


Interlock
 Temperaturbereich: -20°C bis +50°C

- Material:
- Aluminiumgehäuse
 - NBR / FKM (Dichtungen)
 - korrosionsbeständiger Stahl, verzinkter Stahl
 - Messing
 - POM

Air Valve
 Temperatur range: -20°C to +50°C

- Material:
- Housing made of aluminium
 - NBR / FKM (sealing)
 - Stainless steel, zinc coated steel
 - Brass
 - POM



"Copyright protection according to DIN ISO 16016"
 "Schutzvermerk nach DIN ISO 16016 beachten"

ALL TOLERANCED DIMENSIONS ARE FOR INSTALLATION ONLY.
 ALL OTHER DIMENSIONS ARE FOR REFERENCE ONLY.

FMC Technologies

F.A. Sening GmbH, Regentstr. 1, 25474 Ellerbek, Germany

		Date / Datum	Name
Method 1	Method 3	18.06.2010	Larsen
Checked		H. Oelting	

Item name / Benennung
Interlock fuer GPV / Air valve
 made for / zugehörig zu

Scale / Maßst.	1:1	Item-No. / Teile-Nr.	GPVIN
Size / Format	ISO-A4		
Weight / Gewicht	0,3 kg		

Drawing No. / Zeichnungs-Nr.	252498_51	Rev.	00A.00	Sheet / Blatt	1
				of / von	1