FMC Technologies

Configuration (accord. to European MID Regulation)
Meter Package GMVT 805-J
with MultiFlow



	Part-No.	805-01				805-02				805-03			
	Description	Wet Hose Pump				Wet Hose 1+2 Pump				Wet Hose Pump Bypass			
	Product	Diesel		Gasoline		Diesel		Gasoline		Diesel		Gasoline	
	Flow Control 1- or 2-stage (standard or high-low flow)	1	2	1	2	1	2	1	2	1		1	
Meter	GMVT805-J-MID	1	1	1	1	1	1	1	1	1		1	
Gas Extractor Head													
Standard	FH5-MID	1	1			1	1			1			
with pressure switch	FH5-D-MID												
with high capacity vent	FH5E-MID			1	1			1	1			1	
with high capacity vent and pressure switch	FH5E-D-MID												
Valve													
Dry hose	GL80												
Dry hose with non-return valve	GL80-RK												
Dry hose 2-stage,	GL80-M												
Dry hose, non-return valve 2-stage	GL80-RK-M												
Wet hose	GV80	1		1		1		1		1		1	
Wet hose 2-stage	GV80-M		1		1		1		1				
Dry and wet hose	GVL80												
Dry and wet hose 2-stage	GVL80-M												
Dry hose outlet nozzle, 3"	SGA80DO												
Wet hose outlet nozzle	KRW	1	1	1	1					1		1	
Dual wet hose nozzle	DKRW					1	1	1	1				
Bypass valve - not available for 2-stage	B200-3									1		1	
Options:													
Unmetered outlet line valve DN80	DV80-2												
Sight glass for DV80	SGA80/3"												
Wet hose with throttle	GV80-D												
Electronic Meter Head													
MultiFlow, general purpose enclosure	MFLOW-A3-MID	1	1			1	1			1			
MultiFlow, Ex-proof	MFLOW-A1-MID			1	1			1	1			1	
Printer 24V DC, incl. mounting plate and 15 m cable	DR-U295	1	1	1	1	1	1	1	1	1		1	
Temperature probe	PT100SG4/43-V	1	1	1	1	1	1	1	1	1		1	
Chip card	CS-CC-512	1	1	1	1	1	1	1	1	1		1	
Emergency power supplier	MF-EPS	1	1	1	1	1	1	1	1	1		1	
Solenoids 12 Volt, EEx m II T5													
Single	MVS1-E11-12												
Single, 2 Ermeto fittings for plastic seal VS	MVS1-E11-122	1		1		1		1		2		2	
Dual, 2 Ermeto fittings for plastic seal VS	MVS2-E12-122					1	1	1	1				
Dual, 3 Ermeto fittings for plastic seal VS	MVS2-E12-123		1		1		1		1				
Dual, 4 Ermeto fittings for plastic seal VS	MVS2-E12-124												
Plastic seal	VS	4	6	4	6	8	10	8	10	12		12	
Options:													
Printer 24V DC, incl. mounting plate and 15 m cable (for cyrillic character set)	DR-298												

FMC Technologies

Configuration (accord. to European MID Regulation)
Meter Package GMVT 805-J with MultiFlow



	Part-No.	805-04				805-05				805-06			
	Description	Wet Hose 1+2 Pump Bypass				Dry Hose Gravity and Pump				Dry Hose Gravity			
	Product	Diesel		Gasoline		Diesel		Gasoline		Diesel		Gasoline	
	Flow Control 1- or 2-stage (standard or high-low flow)	1		1		1	2	1	2	1	2	1	2
Meter	GMVT805-J-MID	1		1		1	1	1	1	1	1	1	1
Gas Extractor Head													
Standard	FH5-MID	1								1	1		
with pressure switch	FH5-D-MID					1	1						
with high capacity vent	FH5E-MID			1								1	1
with high capacity vent and pressure switch	FH5E-D-MID							1	1				
Valve													
Dry hose	GL80									1		1	
Dry hose with non-return valve	GL80-RK					1		1					
Dry hose 2-stage,	GL80-M										1		1
Dry hose, non-return valve 2-stage	GL80-RK-M						1		1				
Wet hose	GV80	1		1									
Wet hose 2-stage	GV80-M												
Dry and wet hose	GVL80												
Dry and wet hose 2-stage	GVL80-M												
Dry hose outlet nozzle, 3"	SGA80DO					1	1	1	1	1	1	1	1
Wet hose outlet nozzle	KRW												
Dual wet hose nozzle	DKRW	1		1									
Bypass valve - not available for 2-stage	B200-3	1		1									
Options:													
Unmetered outlet line valve DN80	DV80-2												
Sight glass for DV80	SGA80/3"												
Wet hose with throttle	GV80-D												
Electronic Meter Head													
MultiFlow, general purpose enclosure	MFLOW-A3-MID	1				1	1			1	1		
MultiFlow, Ex-proof	MFLOW-A1-MID			1				1	1			1	1
Printer 24V DC, incl. mounting plate and 15 m cable	DR-U295	1		1		1	1	1	1	1	1	1	1
Temperature probe	PT100SG4/43-V	1		1		1	1	1	1	1	1	1	1
Chip card	CS-CC-512	1		1		1	1	1	1	1	1	1	1
Emergency power supplier	MF-EPS	1		1		1	1	1	1	1	1	1	1
Solenoids 12 Volt, EEx m II T5													
Single	MVS1-E11-12												
Single, 2 Ermeto fittings for plastic seal VS	MVS1-E11-122	2		2		1		1		1		1	
Dual, 2 Ermeto fittings for plastic seal VS	MVS2-E12-122	1		1									
Dual, 3 Ermeto fittings for plastic seal VS	MVS2-E12-123						1		1		1		1
Dual, 4 Ermeto fittings for plastic seal VS	MVS2-E12-124												
Plastic seal	VS	16		16		4	6	4	6	4	6	4	6
Options:													
Printer 24V DC, incl. mounting plate and 15 m cable (for cyrillic character set)	DR-298												

FMC Technologies

Configuration (accord. to European MID Regulation)
Meter Package GMVT 805-J
with MultiFlow



	Part-No.	805-07				805-08				805-09				805-10			
	Description	Dry and Wet Hose Gravity and Pump				Dry and Wet Hose 1+2 Gravity and Pump				Dry and Wet Hose Gravity and Pump Bypass				Dry and Wet Hose 1+2 Gravity and Pump Bypass			
	Product	Diesel		Gasoline		Diesel		Gasoline		Diesel		Gasoline		Diesel		Gasoline	
	Flow Control 1- or 2-stage (standard or high-low flow)	1	2	1	2	1	2	1	2	1		1		1		1	
Meter	GMVT805-J-MID	1	1	1	1	1	1	1	1	1		1		1		1	
Gas Extractor Head																	
Standard	FH5-MID																
with pressure switch	FH5-D-MID	1	1			1	1			1				1			
with high capacity vent	FH5E-MID																
with high capacity vent and pressure switch	FH5E-D-MID			1	1			1	1			1				1	
Valve																	
Dry hose	GL80																
Dry hose with non-return valve	GL80-RK																
Dry hose 2-stage,	GL80-M																
Dry hose, non-return valve 2-stage	GL80-RK-M																
Wet hose	GV80																
Wet hose 2-stage	GV80-M																
Dry and wet hose	GVL80	1		1		1		1		1		1		1		1	
Dry and wet hose 2-stage	GVL80-M		1		1		1		1								
Dry hose outlet nozzle, 3"	SGA80DO	1	1	1	1	1	1	1	1	1		1		1		1	
Wet hose outlet nozzle	KRW	1	1	1	1					1		1					
Dual wet hose nozzle	DKRW					1	1	1	1					1		1	
Bypass valve - not available for 2-stage	B200-3									1		1		1		1	
Options:																	
Unmetered outlet line valve DN80	DV80-2																
Sight glass for DV80	SGA80/3"																
Wet hose with throttle	GV80-D																
Electronic Meter Head																	
MultiFlow, general purpose enclosure	MFLOW-A3-MID	1	1			1	1			1				1			
MultiFlow, Ex-proof	MFLOW-A1-MID			1	1			1	1			1				1	
Printer 24V DC, incl. mounting plate and 15 m cable	DR-U295	1	1	1	1	1	1	1	1	1		1		1		1	
Temperature probe	PT100SG4/43-V	1	1	1	1	1	1	1	1	1		1		1		1	
Chip card	CS-CC-512	1	1	1	1	1	1	1	1	1		1		1		1	
Emergency power supplier	MF-EPS	1	1	1	1	1	1	1	1	1		1		1		1	
Solenoids 12 Volt, EEx m II T5																	
Single	MVS1-E11-12																
Single, 2 Ermeto fittings for plastic seal VS	MVS1-E11-122									1		1		1		1	
Dual, 2 Ermeto fittings for plastic seal VS	MVS2-E12-122					1	1	1	1					1		1	
Dual, 3 Ermeto fittings for plastic seal VS	MVS2-E12-123	1	1	1	1	1	1	1	1	1		1		1		1	
Dual, 4 Ermeto fittings for plastic seal VS	MVS2-E12-124		1		1		1		1								
Plastic seal	VS	7	13	7	13	11	17	11	17	10		10		14		14	
Options:																	
Printer 24V DC, incl. mounting plate and 15 m cable (for cyrillic character set)	DR-298																