

## Configuration (accord. to European MID Regulation) Meter Package GMVT 805-SE with MultiFlow and Product Drain Function for Gasoline and Diesel / Heating Fuel

	Part-No.	805SE-07				805SE-08				805SE-09				805SE-10				
	Description			Dry and Wet Hose				Dry and Wet Hose				Dry and Wet Hose				Dry and Wet Hose		
		Gravity and Pump				1+2 Gravity and Pump				Gravity and Pump Bypass				1+2 Gravity and Pump Bypass				
	Product	Die	esel	Gas	oline	Die	esel	Gas	oline	Die	esel	Gasc	oline	Dies	sel	Gaso	oline	
	Control 1- or 2-stage ndard or high-low flow)	1	2	1	2	1	2	1	2	1		1		1		1		
Meter	GMVT805SE-MID	1	1	1	1	1	1	1	1	1		1		1		1		
Gas Extractor Head	1																	
Standard	FH5-MID																	
with pressure switch	FH5-D-MID	1	1			1	1			1				1				
with high capacity vent	FH5E-MID																	
with high capacity vent and pressure switch	FH5E-D-MID			1	1			1	1			1				1		
Valve	1																	
Dry hose	GL80SE																	
Dry hose with non-return valve	GL80SE-RK																	
Dry hose 2-stage	GL80SE-M																	
Dry hose 2-stage, non-return valve	GL80SE-RK-M																	
Wet hose	GV80SE																	
Wet hose 2-stage	GV80SE-M																	
Dry and wet hose	GVL80SE	1		1		1		1		1		1		1		1		
Dry and wet hose 2-stage	GVL80SE-M		1		1		1		1									
Dry hose outlet nozzle, 3"	SGAT80DO	1	1	1	1	1	1	1	1	1		1		1		1		
Wet hose outlet nozzle	KRW	1	1	1	1		H			1		1						
Dual wet hose nozzle	DKRW		Ė		<u> </u>	1	1	1	1					1		1		
Bypass valve -not available for 2-stage	B200-3								<u> </u>	1		1	$\neg$	1		1		
Drain Function	2200 0													•		•		
Controller	EPE2-A1	1	1	1	1	1	1	1	1	1		1		1		1		
Solenoid valve	MVS1-E11-122	1	1	1	1	1	1	1	1	1		1		1		1		
Options:	1		<u> </u>		<u> </u>		<u> </u>	•	<u> </u>					•				
Unmetered outlet line valve DN80	DV80-2																	
Sight glass for DV80	SGAT80/3"												$\neg$		$\neg$			
Wet hose with throttle	GV80-D																	
Electronic Meter Head	1 0.100 2				<u> </u>													
MultiFlow, general purpose enclosure	MFLOW-A3-MID	1	1			1	1			1				1				
MultiFlow, Ex-proof	MFLOW-A1-MID		Ė	1	1		H.	1	1			1		•		1		
Printer 24V DC, incl. mounting plate and 15 m cable	DR-U295	1	1	1	1	1	1	1	1	1		1		1		1		
Temperature probe	PT100SG4/43-V	1	1	1	1	1	1	1	1	1		1		1		1		
Chip card	CS-CC-512	1	1	1	1	1	1	1	1	1		1		1		1		
Emergency power supplier	MF-EPS	1	1	1	1	1	1	1	1	1		1		1		1		
Solenoids 12 Volt, EEx m II T5	1							*		-				•		•		
Single	MVS1-E11-12																	
Single, 2 Ermeto fittings for plastic seal VS	MVS1-E11-122									1		1		1		1		
Dual, 2 Ermeto fittings for plastic seal VS	MVS2-E12-122					1	1	1	1				$\neg$	1		1		
Dual, 3 Ermeto fittings for plastic seal VS	MVS2-E12-123	1	1	1	1	1	1	1	1	1		1	$\dashv$	1	$\dashv$	1		
Dual, 4 Ermeto fittings for plastic seal VS	MVS2-E12-124		1		1		1		1				$\dashv$					
Plastic seal	VS	12	18	12	18	16	22	16	22	15		15		19		19		
Options:	1.0			12			1	13						.0		.5		
Printer 24V DC, incl. mounting plate and	DR-298																	
15 m cable (for cyrillic character set)	511 230																	



## Configuration (accord. to European MID Regulation) Meter Package GMVT 805-SE

## with MultiFlow and Product Drain Function for Gasoline and Diesel / Heating Fuel

