



Model BP-2S



Model BPG-2



Item	Description	Qty.	BP-2S	BPG-2
1	Body, Inlet:			
	Standard.....	1	538710-001	534895-001
	High Viscosity (200 to 20,000 SSU)	1	538710-002	534895-003
	Quick Closure.....	1		534895-002
2	Body, Outlet:			
	NPT, Standard Seals.....	1	519419-001	519419-005
	NPT, PTFE ¹ Seals	1		519419-008
	BSP, Standard Seals	1		519419-007
	BSP, PTFE ¹ Seals	1		519419-009
3	Bushing, Guide	1	533474-001	533474-001
4	Bushing, Valve Stem:			
	Standard.....	1	012383-001	012383-001
	For Use with PTFE ¹	1		536470-002
5	+ Disc, Pilot:			
	Standard.....	1	519425-001	519425-001
	For Use with PTFE ¹	1		519425-002
6	Pin, Groove, 1/8 x 3/4"	1	006127-002	006127-002
7	Piston:			
	Standard.....	1	519423-001	535180-002
	High Viscosity (200 to 20,000 SSU)	1	519423-002	
8	Piston, Back Pressure	1	538756-001	
9	Plate, Retaining	1	519426-001	519426-001
10	Plug, Pipe 1/4" NPT	1		002407-402
11	Plug, Pipe 1/2" NPT	2		006105-002
12	Ring, Internal Retaining	1	644428-401	
13	+ Ring, Quad:			
	Buna-N	1	011702-001	011702-001
	EPR	1	011702-002	011702-002
	@1 PTFE ¹ O-Ring	2		645487-401
	Viton	1	011702-003	011702-003
14	+ Ring, Quad:			
	Buna-N	1	642335-401	
	Viton	1	644427-403	
	EPR	1	644430-401	
15	Screw, #10-32 x 3/8"	1	006045-002	006045-002
16	Screw, 3/8"-16 x 1"	2	060248-002	060248-002
17	Screw, 3/8"-16 x 3-1/4"	2	002086-400	002086-400
18	Screw, #4-40 x 3/16"	3	015603-400	015603-400
19	+ Seat, Pilot:			
	Buna-N	1	519428-001	519428-001
	EPR	1	519428-003	519428-003
	Gylon (In Lieu of PTFE ¹)	1		536471-001
	Viton	1	519428-002	519428-002
20	+ Seat, Valve:			
	Buna-N	1	519427-001	535187-001
	EPR	1	519427-003	535187-003
	Gylon (In Lieu of PTFE ¹)	1		536472-001
	Viton	1	519427-002	535187-002
21	Shaft:			
	Standard.....	1	519433-001	519433-002
	For Use with PTFE ¹	1		519433-003
22	Spring	1	539616-001	
23	Spring	1	533085-001	533085-001
24	Spring	1	519431-001	535172-001
25	Washer, 3/8" Lock.....	4	005791-400	005791-400

¹ Polytetrafluoroethylene (PTFE).

Item	Description	Qty.	BP-2S	BPG-2
26	Washer, #10 Lock	1	642482-406	642482-406
27	Bracket.....	1	533581-001	535693-001
28	Knob	1	006660-001	006660-001
29	Lever	1	533502-001	535692-002
30	+ Link, Connecting.....	1	643377-401	643377-401
31	Pin.....	1	533503-001	535694-001
32	Pin, Roll, 3/32 x 3/4"	1		641767-401
33	Ring, 3/8" Retaining	2	064150-001	
34	Ring, 5/16" Retaining	1	064134-001	064134-001
35	Screw, 5/16"-18 x 1/2"	2	004026-401	004026-401
36	Shaft, Handle	1	518640-001	518640-001
37	Stud	1	004554-001	004554-001
38	Washer, Guide	1	004555-001	004555-001
39	Washer, 5/16" Lock.....	2	642482-407	642482-407

+ Recommended stock.

R Indicates change since last revision.

@1 Place O-Rings on shaft after it has been inserted in body.

Editorial Change: 11/13: Items 2, 4, 5, 13, 19, 20, 21 - reference changed to PTFE.

Headquarters:

500 North Sam Houston Parkway West,
Suite 100, Houston, TX 77067 USA
Phone: +1 (281) 260 2190
Fax: +1 (281) 260 2191

Operations:

Measurement Products and Equipment:
Ellerbek, Germany +49 (4101) 3040
Erie, PA USA +1 (814) 898 5000

Integrated Measurement Systems:
Corpus Christi, TX USA +1 (361) 289 3400
Kongsberg, Norway +47 (32) 286700

The specifications contained herein are subject to change without notice and any user of said specifications should verify from the manufacturer that the specifications are currently in effect. Otherwise, the manufacturer assumes no responsibility for the use of specifications which may have been changed and are no longer in effect.

Contact information is subject to change. For the most current contact information, visit our website at www.fmctechnologies.com/measurementsolutions and click on the "Contact Us" link in the left-hand column.

www.fmctechnologies.com/measurementsolutions